



INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(51) International Patent Classification ⁵ : A61J 1/06, 1/00, A61M 5/24	A2	(11) International Publication Number: WO 94/21213 (43) International Publication Date: 29 September 1994 (29.09.94)
---------------------------------------------------------------------------------------	----	-------------------------------------------------------------------------------------------------------------------------

(21) International Application Number: PCT/US94/02738

(22) International Filing Date: 14 March 1994 (14.03.94)

(30) Priority Data:
08/031,683 15 March 1993 (15.03.93) US

(71) Applicant: ELI LILLY AND COMPANY [US/US]; Lilly Corporate Center, Indianapolis, IN 46285 (US).

(72) Inventor: HARRIS, Dale, C.; 4699 North Frontage Road, Fairland, IN 46126 (US).

(74) Agents: HOFFMAN, John, F. et al.; Baker & Daniels, 2400 Fort Wayne National Bank Building, Fort Wayne, IN 46802 (US).

(81) Designated States: AT, AU, BB, BG, BR, BY, CA, CH, CN, CZ, DE, DK, ES, FI, GB, HU, JP, KP, KR, KZ, LK, LU, LV, MG, MN, MW, NL, NO, NZ, PL, PT, RO, RU, SD, SE, SK, UA, UZ, VN, European patent (AT, BE, CH, DE, DK, ES, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, ML, MR, NE, SN, TD, TG).


Published

Without international search report and to be republished upon receipt of that report.

(54) Title: CARTRIDGE ASSEMBLY FOR A LYOPHILIZED COMPOUND FORMING A DISPOSABLE PORTION OF AN INJECTOR PEN AND METHOD FOR SAME

(57) Abstract

A cartridge assembly (90) for holding a lyophilized product, forming a disposable portion of a pen injector (104), includes a cylindrical glass cartridge (58) adapted to receive the product, a closure cap (20), a cartridge case (76), and a plunger mechanism. The closure cap (20) is adapted to retain an elastomeric disc seal (52) during lyophilization and includes diametrically opposed ledges (38, 40). The closure cap (20) and seal (52) are adapted to cover a neck portion of the ampule (58), the neck portion having on its end a radially extending circumferential flange (62). The ledges (38, 40) of the closure cap (20) and the flange (62) of the neck portion allow the closure cap (20) to remain open during lyophilization, oxygen purge and nitrogen overlay. An oval-shaped indentation formed on the inside of the closure cap (20) aids in snapping the closure cap (20) about the flange (62) without crimping to retain the closure cap (20) underneath the flange (62). Reconstitution of the lyophilized drug is accomplished without foaming by use of an obliquely angled connector (30) which causes the diluent to indirectly impinge on the drug. The injection pen (104) and cartridge assembly (90) cooperate such that the length of travel of the plunger rod (108) during retraction is less than the axial length of a recess (107) in the rod tip (73).



FOR THE PURPOSES OF INFORMATION ONLY

Codes used to identify States party to the PCT on the front pages of pamphlets publishing international applications under the PCT.

AT	Austria	GB	United Kingdom	MR	Mauritania
AU	Australia	GE	Georgia	MW	Malawi
BB	Barbados	GN	Guinea	NE	Niger
BE	Belgium	GR	Greece	NL	Netherlands
BF	Burkina Faso	HU	Hungary	NO	Norway
BG	Bulgaria	IE	Ireland	NZ	New Zealand
BJ	Benin	IT	Italy	PL	Poland
BR	Brazil	JP	Japan	PT	Portugal
BY	Belarus	KE	Kenya	RO	Romania
CA	Canada	KG	Kyrgyzstan	RU	Russian Federation
CF	Central African Republic	KP	Democratic People's Republic of Korea	SD	Sudan
CG	Congo	KR	Republic of Korea	SE	Sweden
CH	Switzerland	KZ	Kazakhstan	SI	Slovenia
CI	Côte d'Ivoire	LI	Liechtenstein	SK	Slovakia
CM	Cameroon	LK	Sri Lanka	SN	Senegal
CN	China	LU	Luxembourg	TD	Chad
CS	Czechoslovakia	LV	Latvia	TG	Togo
CZ	Czech Republic	MC	Monaco	TJ	Tajikistan
DE	Germany	MD	Republic of Moldova	TT	Trinidad and Tobago
DK	Denmark	MG	Madagascar	UA	Ukraine
ES	Spain	ML	Mali	US	United States of America
FI	Finland	MN	Mongolia	UZ	Uzbekistan
FR	France			VN	Viet Nam
GA	Gabon				

CARTRIDGE ASSEMBLY FOR A LYOPHILIZED COMPOUND
FORMING A DISPOSABLE PORTION OF AN
INJECTOR PEN AND METHOD FOR SAME

The present invention relates to the sealing and
5 dispensing of pharmaceuticals and, more particularly to
the sealing and dispensing of a lyophilized drug in a
cartridge assembly.

In current technology, drugs or compounds
manufactured for various injections are generally
10 encapsulated in sterile glass cartridges. The glass
cartridges characteristically have a sealed end with the
other end of the cartridge generally having a restricted
opening in the form of a neck having a circumferential
flange. The opening can be closed off with a rubber
15 membrane held into place with an aluminum seal crimped
therearound. Where the drug or compound is to be later
dispensed either directly from the cartridge or in a
dispensing device such as a pen dispenser, the cartridge
includes at the end opposite the restricted opening, an
20 open end generally having a rubber plunger closing the
open end. The rubber plunger also acts as a piston to
force the drug or compound contained within the cartridge
out of the restricted opening into which there has
generally been inserted a cannula, by action of a plunger
25 rod exerting axial pressure upon the rubber plunger.

Cartridges for use with dispenser devices or pens as
described above are generally known in the prior art.
U.S. Patent 4,936,833 Sams, shows a typical glass
cartridge having an open end with a plunger therein, and
30 an opposite end including a restricted opening sealed with
a rubber membrane and crimped metal collar. The cartridge
is insertable into a housing forming a part of a dispenser
pen, with a cap for receiving a two ended cannula.
Typical of these device are U.S. Patent 4,883,472 Michel,
35 and U.S. Patent 4,973,318 Holm et al.

Lyophilized drugs or compounds are currently being
utilized as the basis for injectionable compounds, such as

human growth hormone (HGH), insulin, and the like. Lyophilization is the rapid freezing of a material at a very low temperature followed by rapid dehydration by sublimation in a high vacuum. The lyophilized compound is generally contained in a glass vial or cartridge. However, the process described above is not suitable for lyophilized compounds which are moisture and oxygen sensitive. When the moisture is removed from the compound during lyophilization, the oxygen in the glass cartridge containing a lyophilized drug must be replaced with nitrogen after the lyophilization process. This step of replacing the oxygen with nitrogen is termed nitrogen overlay and is accomplished within the lyophilizing chamber (freeze dryer).

One technique is to lyophilize the drugs or compounds in rubber stoppered glass vials. During lyophilization of the compounds in the glass vials, the rubber stopper used to close the vial is partially seated in the neck of the vial. The moisture which is removed from the compound during lyophilization is vented out through grooves or slots formed in the rubber stopper. As a general method of closing the vials, the shelves of the lyophilization chamber vertically move together to press the rubber stopper down into the vial, until the vents in the stopper are well inside the neck opening of the vial. An aluminum seal is then crimped about a flange on the neck of the vial.

The use of aluminum as a crimping seal for the rubber stopper is not, however, preferred due to the possibility of aluminum dust or particles contaminating the compound during the initial crimping, reconstitution, or administration processes. In addition, such processes as above are not well suited for efficient lyophilization.

Thus, it is desired to eliminate the aluminum crimping seal as well as provide an easier method of assuredly allowing lyophilization of a compound and sealing the same.

In order to administer a lyophilized compound, it is necessary to reconstitute the compound prior to administration with a suitable diluent. Reconstitution is accomplished by using a syringe with a needle to withdraw the diluent from a separate vial and inject it into the vial containing the lyophilized compound. The vial containing the lyophilized compound is placed in a holder during reconstitution. Because the cartridge is filled with the lyophilized compound and nitrogen, addition of the diluent produces extra pressure within the cartridge which creates the possibility of forcing the plunger out of the cartridge. Having the plunger forced out of the cartridge during reconstitution would undesirably result in a total loss of the compound.

During reconstitution, the diluent injected from the syringe into the cartridge directly impinges upon the lyophilized compound which causes the lyophilized compound to foam. The foam undesirably creates extra head space within the cartridge such that the proper amount of diluent is not mixed with the compound, resulting in an improper diluent to compound ratio. In order to alleviate this, one must wait for the foam to subside.

A patient needle is then attached to the disc sealed end of the cartridge which thus allows the compound to be injected. Current injector pens dispense a selectable amount of drug depending on the required dosage. A plunger mechanism, including a plunger rod, pushes against the plunger in the cartridge. After each injection, the plunger mechanism and plunger rod retract during a resetting function of the injector pen. However, complete disengagement of the plunger rod from the plunger mechanism during retraction is highly undesirable, and can render the injector pen inoperative.

Because of the expanding use of pen dispensers or injectors utilizing cartridges for the administration of injectionable compounds, it is desired to provide a

lyophilized compound in an improved cartridge suitable for use in an injector pen.

The present invention, in one form thereof, provides a method of lyophilizing a compound in a glass cartridge and sealing the same utilizing a closure cap with a seal, and encapsulating the same into a cartridge assembly.

A method of lyophilizing and sealing an injectionable product within a cartridge is provided which includes, providing a cartridge having a neck defining a first opening therein, and a second opening therein distal the first opening, the neck including a circumferential radially outwardly extending flange adjacent the first opening, inserting a plunger in the second opening, and inserting the product to be lyophilized into the cartridge. Further, there is provided a cap having a cylindrical portion and a seal, the cylindrical portion including an open bottom receivable over the neck, the cap including a top having an opening therein for receipt of a needle therethrough, at least one vent circumferentially disposed in the cap, and a deformable ledge in the cap extending radially inwardly from the cylindrical portion axially below the vent, the seal being axially disposed between the vent and the top so as to block the top opening. The cap is then placed onto the neck such that the deformable ledge rests upon the neck flange and the vent is in communication with the neck opening, after which the cartridge with the cap is placed in a lyophilizing chamber, wherein the product is lyophilized, and the cap is closed by exerting a downward pressure upon the cap such that the deformable ledge yieldably snaps around the neck flange to be lockingly retained thereunder, the vent is closed from communication with the neck opening, and the seal is compressed into sealing engagement with the neck opening by downward pressure exerted by the top thereby providing an air impermeable barrier between the top opening and the neck opening.

The method of sealing a lyophilized product within a cartridge is further characterized by providing a sleeve having a first open end and a radially inwardly extending circumferential ledge into which the cartridge is placed.

- 5 The cartridge is axially seated against the ledge and the sleeve is permanently attached to the cap.

A plunger rod tip having a plunger head is received in the sleeve between the plunger and ledge such that the plunger head is axially adjacent the plunger.

- 10 The present invention, in one form thereof, provides a cartridge assembly containing a lyophilized drug having a cartridge, a cap and seal, a cartridge sleeve, and a plunger mechanism forming a disposable portion of an injector pen.

- 15 A cartridge assembly for holding a lyophilized drug and forming a disposable part of an injection pen comprises a cartridge having a plug in one end and a neck on another end, the cartridge including a circumferentially extending flange about the neck, the
20 neck defining an opening therein, a cap disposed about the neck, the cap having a first cylindrical portion including an open bottom received over the neck, a top having an opening therein for receipt of a needle therethrough, and a deformable ledge extending radially inwardly from the
25 first cylindrical portion and lockingly retained under the neck flange. A resilient seal is disposed in the cap between the neck opening and the top opening forming an impermeable barrier therebetween, with a sleeve radially disposed about and permanently attached to the cartridge.

- 30 Further, the sleeve is permanently attached to the cap, and includes a first cylindrical portion adapted to receive the cartridge and a second cylindrical portion axially below the first cylindrical portion and concentric therewith, and a radially inward circumferentially
35 extending ledge defined at the junction of the first and second cylinder for axially retaining the one end of the cartridge.

In one form thereof the present invention provides a method and apparatus for reconstituting a lyophilized compound, the lyophilized compound contained within an interior space defined by an inner wall of the cartridge having an inlet at one end thereof. The method comprising the step of injecting a diluent into the cartridge via the inlet such that the diluent impinges on and runs down the inner wall of the cartridge to thereby contact the compound, whereby foaming of the compound is alleviated.

5 A connector is releasably secured to the inlet end of the cartridge and adapted to receive and hold a syringe containing a diluent. The connector has a first portion defining a longitudinal axis which forms an oblique angle with the longitudinal axis of the cartridge. The syringe is supported by the connector at the oblique angle whereby the diluent is injected into the cartridge via the inlet at the oblique angle so that the diluent impinges on the wall of the cartridge.

The cartridge of the present invention is adapted to be used with an injector pen apparatus for administering a drug. The apparatus comprises a cartridge assembly having a cartridge with a movable plunger therein and an inlet on one end thereof. The cartridge assembly includes a rod tip having a recess therein and disposed axially adjacent the plunger and is adapted to exert pressure upon the plunger for dispensing the drug from the cartridge. An injector pen is releasably engaged with the cartridge assembly, the pen including a movable rod adapted to engage the recess of the rod tip in order to move the rod tip during dispensing of the drug. For injection of the drug, the rod retracts a known distance away from the plunger within the recess of the rod tip. The rod is then advanced towards the plunger a selected number of discrete increments as determined by the number of clicks depending on the desired dosage to be administered. During injection, the rod then advances the known distance towards the plunger which causes the plunger to advance

the distance determined by the amount of discrete increments. The rod then retracts the known distance within the travel length of the rod tip.

5 It is an advantage of the present invention that the closure cap does not require close tolerances in cartridge manufacture.

It is another advantage of the present invention in that the cartridge, closure cap with seal, and cartridge case with plunger form a tamper resistant package.

10 It is yet another advantage of the present invention that the cartridge assembly prevents the plunger from outwardly moving during shipment of the cartridge assembly and during reconstitution of the lyophilized drug contained therein.

15 It is further an advantage of the present invention that foaming of the lyophilized compound is prevented during reconstitution thereof.

It is still another advantage of the present invention in that the cartridge assembly is protected from
20 breakage.

It is also an advantage of the present invention that container integrity for the drug is increased.

The above mentioned and other features and objects of this invention, and the manner of attaining them, will
25 become more apparent and the invention itself will be better understood by reference to the following description of embodiments of the invention taken in conjunction with the accompanying drawings, wherein:

Fig. 1A is a perspective view of the closure cap
30 according to an aspect of the present invention;

Fig. 1B is a bottom view of the closure cap taken along line 1B-1B of Fig. 2;

Fig. 2 is a sectional elevational view of the closure cap taken along line 2-2 of Fig. 1A;

35 Fig. 3 is an elevational cutaway view of the glass cartridge and plunger;

Fig. 4 is an elevational cutaway view of the glass cartridge with plunger seated on a shelf with the closure cap in an open condition;

5 Fig. 5 is an elevational cutaway view of the glass cartridge with plunger seated on a shelf with the closure cap in a closed position;

Fig. 6 is an elevational cutaway view of a cartridge assembly with user needle and cap;

10 Fig. 7 is an elevational cutaway view of the cartridge assembly according to an embodiment of the present invention;

Fig. 8 is a partial cutaway view of the cartridge assembly according to an embodiment of the present invention installed on a dispensing pen unit;

15 Fig. 9 is an elevational cutaway view of the cartridge assembly during reconstitution;

Fig. 10 is an elevational cutaway view of the cartridge assembly with connector and connector lid before insertion into a dispensing pen and reconstitution;

20 Fig. 11 is a partial cutaway view of the cartridge assembly installed on a dispensing pen; and

Figs. 12-14 are partial cutaway views of the plunger and rod mechanism as utilized with the dispensing pen illustrating the injection process.

25 Corresponding reference characters indicate corresponding parts throughout the several views. The exemplifications set out herein illustrate a preferred embodiment of the invention, in one form thereof, and such exemplifications are not to be construed as limiting the scope of the invention in any manner.

30 Referring now to Figs. 1A, 1B, and 2, there is shown a closure or lyophilization cap 20 in accordance with an aspect of the present invention. In general, cap 20 is preferably made of an injection molded plastic, although
35 other suitable materials as known in the art may be utilized with the cap thus fabricated accordingly. Cap 20 has a cylindrical bottom portion or skirt 22 of a given

axial length and inner radius sufficient to extend about at least a portion of a lyophilization cartridge. As further described hereinbelow, bottom portion or skirt 22 stabilizes cap 20 when placed onto cartridge 58 in the open position during lyophilization, and serves as a guide during closing of the cap. Cylindrical bottom portion 22 has a slightly upwardly and inwardly sloping annular shoulder 24, with a cylindrical top portion or neck 26 disposed axially above and inwardly concentric to cylindrical bottom portion 22. Top portion 26 includes threads 28 circumferentially formed on the outer upper periphery thereof which are adapted to threadedly receive a connector 30 (Figs. 9 and 10) and needle assembly 32 (Fig. 6) both of which are described in more detail hereinbelow. Formed in cylindrical top portion 26 below threads 28 are two diametrically opposed circumferentially extending rectangular openings 34 and 36 which serve to vent moisture from cartridge 58 (Figs. 3-5) during lyophilization and which allow the oxygen purge and nitrogen overlay process to occur thereafter.

As best seen in Fig. 1B, extending radially inward from wall 33 and 35 just below openings 34 and 36 are two ledges 38 and 40 having a circumferential length roughly corresponding to openings 34 and 36. As will be described in more detail hereinbelow, ledges 34 and 36 serve the dual function of allowing closure cap 20 to be seated upon cartridge 58 thus permitting communication between openings 34, 36 and the interior 60 of cartridge 58, and of snapping around and under circumferential flange 62 of cartridge neck 64 upon closing cap 20. Ledges 38 and 40 are sized and shaped so as to reduce the closing pressure required during the closing process, described hereinbelow, and to minimize the amount of cap deformation as closure is taking place. Cap 20 includes a top 41 which downwardly slopes from the outer upper edge of cylindrical top portion 26 terminating at an aperture 46 adapted to expose a seal 52 and receive a needle as

described in detail hereinbelow. Two arched slots 42 and 44 are disposed in top portion 41 each axially upwardly of a respective side opening 34, 36. Arched slots 42 and 44 are formed during the molding process in order to achieve the undercut ledges 38 and 40 sufficiently large enough to allow for variations in the diameters of cartridge flanges.

Defined at the level 50 of ledges 38, 40 interior to cap 20 are walls 33, 35, 47, and 48 that define an oval or elliptic surface 49 whose major axis is transverse to an axis defined by connecting the middle of side openings 34, 36 or ledges 38, 40 such that each longitudinal end of oval or ellipse 49 is located 90° from each ledge 38 and 40. Walls 47 and 48 are thinner than walls 33 and 35 carrying ledge 38 and 40 so that as the ledges are forced outwardly during seating of cap 20, walls 47, 48 can move inward to accommodate such outward movement of walls 33 and 35 carrying ledges 38, 40. However, the thicker walls 33, 35 provide adequate support for ledges 38, 40 to prevent dislodgement of cap 20 from cartridge 58. This reduces the pressure required to close cap 20 onto cartridge 58 after lyophilization and nitrogen purge in order to prevent stress fractures in cap 20 and allow for more cartridges to be closed at one time. Such elliptical configuration of walls 33, 35, 47 and 48 extends the entire inner axial length thereof.

A circumferential ridge 51 is disposed about the interior of cylindrical top portion 26 axially below and adjacent top 41. Ridge 51 permits seal 52, such as for instance a laminated, two-piece rubber seal, to be seated therein without dislodging for efficient covering of opening 46.

The structure of cap 20 assists the natural deformation that occurs during the closure process. Thus, as cap 20 is pressed onto cartridge 58, ledges 38, 40 spring outward to allow it to go over and then underneath neck flange 62 (see Fig. 3).

What has thus been described hereinabove is a cap adapted to be seated upon a cartridge during lyophilization and which effectively and positively closes upon the cartridge to securely hold a disc seal about the opening. The cap is designed for efficient lyophilization and optimal nitrogen sealability while requiring only a minimum amount of closure force.

The process of lyophilizing a compound in cartridge 58 utilizing the hereinabove described cap 20 will now be described in conjunction with Figs. 3-5. First, it should be noted that the various parts are sterilized prior to placement in the freeze dryer so that the compound to be lyophilized will be free from contamination. Secondly, it should be noted that a plurality of cartridges (up to 6000 or more) are generally lyophilized at one time. The cartridges are held in blocks defining a matrix of rows and columns of cartridges with the blocks placed in a freeze dryer chamber between movable shelve units, described hereinbelow. A typical configuration is 2000 per layer with three layers. The general structure of the various elements will also be described when introduced during the description of the process.

Cartridge 58 is manufactured of glass and consists of a tube portion 59 defining an inner chamber 60 and which openly terminates at one end with a circumferential inwardly bulbous lip 56. The other end of tube 59 includes an upwardly and inwardly sloping shoulder portion 66, a reduced diameter neck 64 and a rim 63 having circumferential flange 62 having a circumferential radius greater than that of neck 64. The end of cartridge 58 including flange 62 defines an opening 68 which communicates with inner chamber 60. Recessed neck 64 has a diameter that is smaller than shoulder 66. A rubber plunger 54 having knobs 55 is first disposed in the end having lip 56 just far enough into cartridge 58 such that the end of plunger 54 is adjacent lip 56. This is to keep the inside of cartridge 58 sterile after lyophilization.

Cartridge 58 with plunger 54 is placed between shelves 72 and 74 in the freeze dryer (not shown) with the liquid compound or drug 70 to be lyophilized contained therein. Cap 20 having rubber disc seal 52 disposed
5 therein is placed over flange 62 defining a first or open position, the placement of cap 20 onto cartridge 58 occurring either before placement of cartridge 58 into the freeze dryer or thereafter. However, compound 70 is placed into cartridge 58 before the placement of cap 20
10 upon flange 62. Seal 52 is preferably a laminate of two different materials, the upper material 52a being a good sealing material, with the bottom material 52b being a good product contact material such as, for example, a normal butyl rubber compound. However, any resilient
15 sealing material may be utilized which provides a good product contact material on the bottom and a good sealing material on the top.

Referring specifically to Fig. 4, cap 20 is designed such that ledges 38 and 40 rest on top of flange 62. In
20 the first or open position a part of cylindrical bottom portion 22 circumferentially surrounds an upper part of tube 59 thereby serving as a stabilizer for cap 20 and a guide when cap 20 is moved to the second or closed position. Seal 52 is held in an elevated position above
25 cartridge opening 68, while side openings 34 and 36 are above opening 68 thus allowing communication between the ambient atmosphere and inner chamber 60 of cartridge 58. At this point lyophilization begins.

Lyophilization, or freeze drying, which is
30 represented in Fig. 4 as an upward and outward arrow, purges the moisture from compound 70 such that a waterless compound is left. Although the arrow is shown exiting only one side opening 36, it should be understood that the moisture is vented out through both openings 34, 36 during
35 lyophilization. Once the moisture has been vented out of cartridge 58, oxygen is purged from the lyophilization chamber and thus cartridge 58. A nitrogen overlay process

is then initiated. The nitrogen overlay process is represented in Fig. 4 as an inward and downward arrow entering from side opening 34, but as is the case for the venting of moisture and oxygen purge, the nitrogen enters through both side openings 34 and 36 to fill the entire inner space 60 of cartridge 58 not occupied by the now lyophilized compound 70. The nitrogen overlay process is used where the lyophilized compound is oxygen sensitive, as, for example, HGH.

At this point and referring now to Fig. 5, shelves 72 and 74 move vertically together in order to close cap 20 onto neck 64. As described above, cap 20 includes an oval or elliptical indentation 47 and inner wall 48 which allows cap 20 and ledges 38 and 40 to deform and flex so that ledges 38 and 40 snap around flange 62 as cap 20 is downwardly pressed by the pressure exerted by closing shelves 72 and 74. A force of only about 10-12 lbs. is thus necessary to effect closure of cap 20 about neck 64 and neck flange 62. Once in place, cylindrical bottom portion 22 extends about an upper part of tube 59, while ledges 38 and 40 prohibits removal of cap 20 by extending under neck flange 62 between the flange and sloped shoulder section 66.

Upon closure of cap 20, seal 52 is compressed between the top of rim and downwardly sloped cap top 41 to effect a positive, airtight seal between the ambient atmosphere and the nitrogen and lyophilized compound within cartridge 58. There is no need for a crimp seal, while both the lyophilization and closure processes are completed within the lyophilizing chamber. At this point, the sealed cartridge may be removed from the lyophilizing chamber. A cake or plug of compound 70 is thus sealed within a nitrogen filled cartridge.

After lyophilization, and referring to Fig. 7, sealed cartridge 58 is then placed into a cartridge sleeve, barrel, or retainer 76 through an opening 77 in one end thereof. The sleeve is preferably made from a suitable

plastic or other material which provides protection for the glass cartridge.

Sleeve 76 comprises a first tubular portion 78 having an inner diameter 79 of sufficient size such that a
5 segment of first tubular portion 78 radially surrounds or overlaps cylindrical bottom portion 22 of cap 20. At this junction, sleeve 76 is attached or sealed to cap 20 by use of a solvent, adhesive bond, snap fit, sonic weld, or the like, such that cartridge 58 is retainingly held in sleeve
10 76. Sleeve 76 also includes a second tubular portion 80 having a smaller diameter than first tubular portion 78 such that tube 59 of cartridge 58 is inwardly circumjacent the inner diameter thereof. Threads 86 on the outer periphery of second tubular portion 80 permit sleeve 76 to
15 be received onto an injection pen device.

Sleeve 76 further comprises a third tubular portion 82 having a smaller diameter than second tubular portion 80, the second tubular portion defining an annular stop or ledge 84 at the junction of second and third tubular
20 portions 80 and 82. Stop 84 supports lip 56 such that tube 59 is supported thereon. A sleeve cap 88 optionally may fit about the top of the cartridge assembly 90 to further protect the seal assembly. Thus, the cartridge is securely held by and contained within sleeve 76 and ready
25 for reconstitution before administration and placement into an injector pen dispenser.

Sleeve 76 has a smaller diameter opening 69 at the other end through which extends a plunger rod tip 71. Rod tip 71 is placed within sleeve 76 before insertion of
30 cartridge 58, and has a circular rod head 73, slightly less than the inner diameter of cartridge 58, on one end of a hollow cylindrical body 85. The lower portion of rod head 73 is seated against sleeve ledge 84 and is of sufficient diameter such that rod tip 71 is retained in
35 sleeve 76. Rod tip body 85 is of sufficient length to axially extend from head 73 to the axial end of third tubular portion 82. Cylindrical body 85 defines an

axially elongated cylindrical recess or bore 107. Recess 107 defined by cylindrical body 85 between bottom portion 81 of rod head 73 and end portion 83 is of a specific axial length, for example, eight and nine tenths millimeters (8.9 mm). The upper surface of circular rod head 73 of rod tip 71 abuts plunger 54 and includes an annular groove 75 into which knobs 55 of plunger 54 are seated. As pressure is applied to plunger 54 in order to administer the reconstituted compound, plunger 54, being an elastomeric or rubber, has a tendency to deform during compression. However, because of its resiliency, plunger 54 returns to its original shape, which sequence could cause weeping of the liquid from around the plunger. Rod head 73 serves to distribute the load exerted by the compression of rod tip 71 in order to eliminate weeping from about plunger 54 which could occur as a result of uneven or localized compression of plunger 54. Annular groove 75 retains knobs 55 to prevent lateral deformation, which could cause weeping.

As shown in Fig. 10, a connector 30 is threadedly attached to threads 28 of cap 20. This occurs after placement of cartridge 58 in sleeve 76 and attachment of cap 20 thereto. Connector 30, introduced hereinabove, is threadedly attached to threads 28 of cap 20 and includes an angled first section 92 and a larger diameter second section 94. First section 92 is tubular in shape and includes an upper section 111 and, at its lower end, an angled neck portion 113 having mating threads for threads 28. Neck portion 113 is essentially concentric and defines a common axis with cartridge 58. Upper section 111 defines an axis which thus forms an oblique angle with the axis of neck portion 113. Larger diameter portion 94 is eccentric with upper section 111 of first section 92. A common axis is also defined between upper section 111 and portion 94.

A lid 95 is snapped in place over cylindrical second section 94 thereby sealing the space there between. This

entire assembly is then sterilized so that the contents of the cartridge and the area about the disc seal is sterile for later reconstitution and administration.

Reconstitution is performed as shown in Fig. 9.

- 5 After removal of connector lid 95, connector 30 is thus adapted to receive a syringe 96 in second section 94 which supports syringe 96 but allows needle 98 to enter hole 46 and penetrate seal 52 such that only a small section of needle 98 extends into cartridge 58. During
- 10 reconstitution, the action produced by the force of moving diluent upon the lyophilized cake (e.g. HGH) triggers a reaction which causes the HGH cake to become agitated and foam. Foaming undesirably creates air bubbles, thereby limiting the amount of diluent that can be added to the
- 15 cartridge. This can result in improper dilution ratios of the lyophilized compound. Furthermore, once the foam subsides, too large a headspace is created within the cartridge.

- According to one aspect of the present invention,
- 20 connector 30 is obliquely angled as described above such that needle 98 is oriented toward and preferably in close proximity to wall 58 and injects diluent 102 down the side of the interior wall of cartridge 58 in order to prevent foaming of the compound during the reconstitution process.
- 25 Side impingement of the diluent reduces the velocity of the diluent as it travels toward and onto the HGH cake. This indirect administration of the diluent by causing the diluent to impinge on the inner side wall of cartridge 58 and then run down around and into the HGH prevents
- 30 foaming.

- Syringe 96 is prefilled with a suitable diluent 102, and as plunger 100 of syringe 96 forces fluid into the lyophilized cartridge, the nitrogen in cartridge 58 is compressed. Releasing syringe plunger rod 100 while
- 35 holding the syringe above the cartridge, allows the pressure in the cartridge to equilibrate by venting the nitrogen into the syringe, leaving the diluent in the

cartridge to mix with the lyophilized drug. The syringe is then removed and discarded.

A transfer needle 32, such as those manufactured by Becton-Dickinson, can then be threadedly attached to cap
5 20 where connector 30 was attached during reconstitution. This is shown in Fig. 6. The typical transfer needle 32 is a double-ended needle 110, which extends in one direction through hole 46 in top 41 and seal 52 to communicate with the reconstituted drug within the
10 cartridge. Needle 110 is secured in a needle housing 112 and protected during nonuse by a plastic cap 114 and needle assembly protector cap 116.

Referring in particular now to Fig. 8, cartridge assembly 90 is threadedly attached to an injector pen 104,
15 such as that manufactured by Disetronic AB of Burgdorf, Switzerland. A plunger rod 108 fits into recess 107 of rod tip 71 in order to effect ejection of the reconstituted drug from the cartridge. The inside length of rod tip 71 is adapted to retain the injector pen
20 plunger rod 108 during the injector pen's compression and retraction stroke. When the drug is to be administered to the patient, the needle assembly 32 as shown in Fig. 6 is attached to cap 20 as described hereinabove.

One such type of injector pen is shown in Fig. 11 and
25 its operation described in conjunction with additional Figs. 12-14. Referring to Fig. 11, cartridge assembly 90 is shown connected to injector pen 104 via complementary threads 86, 101. Injector pen 104 includes a pen rod 108, a dose knob 118 and a release button 120. Pen rod 108
30 fits into a suitable mechanism within pen body 106 for providing the injector function as described below in conjunction with Figs. 12-14.

It should be noted with respect to Figs. 12-14 that for simplicity of discussion and understanding of an
35 aspect of the present invention that only rubber plunger 54 and plunger rod tip 71 of the cartridge assembly are shown in relationship to pen 104 and, in particular pen

rod 108. To load the assembly for the first time, release button 120 is pushed such that dose knob 118 pops out. At this point, pen rod 108 retracts a known, or predetermined distance, for example 8.1 millimeters away from plunger 54 within recess 107. Dose knob 118 is then turned until dose knob 118 stops which causes pen rod 108 to travel forward towards plunger 54 a set maximum amount for purging. Upon retraction, pen rod 108 cooperates with rod tip 71 in that pen rod 108 does not travel any more than 8.1 millimeters out of the 8.9 mm (for example) recess 107 of the rod tip 71. End 109 of plunger rod 108 thus never retracts past a plane defined at the end 83 of rod tip 71 perpendicular to an axis of elongation of rod tip 71. Thus, rod 108 never disengages from recess 107.

The rod tip, being an integral part of the housing for the cartridge assembly prevents the plunger 54 in the cartridge from being forced out during the reconstitution process. Further, rod tip 71 allows movement required by the pen's plunger rod 108 during dose setting and injection. When dose knob 118 is pushed in, the unit purges 95 percent of all of the air in the cartridge in order to obtain a proper head space. Thus, after reconstitution, and initial purging, the injector pen assembly is ready for the administration process as shown in Fig. 11.

In order to administer the drug to the patient, release button 120 is pressed which causes dose knob 118 to pop out and correspondingly cause pen rod 108 to retract the 8.1 mm maximum travel distance within the 8.9 mm rod tip 71, each action being depicted by respective arrows in Fig. 12. As noted hereinabove, end 109 never retracts past end 83. Dose knob 118 is then turned through so many clicks, the clicks corresponding to volume units of dosage depending on the required amount of dosage. Each click corresponding to a given volume of injectionable liquid. This is depicted in Fig. 13. As the required number of clicks are set via dose knob 118,

pen rod 108 correspondingly moves forward an amount equal to the number of clicks; with each click correspondingly moving pen rod 108 a predetermined distance being coordinated with a set dosage amount.

5 As shown in Fig. 14, when dose knob 118 is depressed, pen rod 108 thus contacts rod head 73 of rod tip 71 to administer the drug by traveling the 8.1 mm distance. Upon retraction of pen rod 108 in order to administer another dose, pen rod 108 retracts the set 8.1 mm distance
10 within the 8.9 mm recess 107. This ensures that pen rod 108 never comes out of rod tip 107.

 The process as depicted in Figs. 12-14 is repeated at the prescribed times until all of the drug has been administered. A dose indication device 122 is provided to
15 visually indicate the dosage set by dose knob 118. Such dose indication may be purely mechanical in nature or electronic, such as an LCD display.

 Once the entire drug has been administered to the patient, the entire cartridge assembly and patient needle
20 assembly is then discarded. The injector pen is then ready for another cartridge assembly 90.

 While this invention has been described as having a preferred design, the present invention can be further modified within the spirit and scope of this disclosure.
25 This application is therefore intended to cover any variations, uses, or adaptations of the invention using its general principles. Further, this application is intended to cover such departures from the present disclosure as come within known or customary practice in
30 the art to which this invention pertains and which fall within the limits of the appended claims.

CLAIMS

1. A method of lyophilizing and sealing an injectionable product within a cartridge, the method comprising the steps of: providing an elongate cartridge (58) having on a first end thereof a shoulder (66), a rim (63) defining a first opening and having a circumferential radially outwardly extending flange (62) adjacent said first opening, and a neck (64) disposed axially between said flange and shoulder, said neck having a diameter smaller than said flange and shoulder, said cartridge including a second opening on a second end thereof distal said first opening; and inserting a plunger (54) in said second opening; characterized by:

providing a cap (20) having a cylindrical portion and a seal (52), said cylindrical portion including an open bottom receivable over said neck, said cap including a top having an opening therein for receipt of a needle therethrough, at least one vent (34) circumferentially disposed in said cap, and at least two deformable ledges (38,40) on said cap extending radially inwardly from said cylindrical portion axially below said vent, said seal being axially disposed between said vent and said top so as to block said top opening;

inserting the product to be lyophilized into said cartridge (58);

placing said cap onto said cartridge such that said deformable ledges (38,40) rest upon said flange (62) and said vent is in fluid communication with said cartridge first opening; placing said cartridge with said cap in a lyophilizing chamber; lyophilizing the product; and

closing said cap by exerting a downward pressure upon said cap such that said deformable ledges yieldably snap around said flange (62) and into said neck to be lockingly retained therein, said vent (34) is blocked from communication with said cartridge first opening, and said seal (52) is pressed into sealing engagement with said rim (63) by downward pressure exerted by said top thereby

providing an air impermeable barrier between said top opening and said cartridge first opening.

2. The method of claim 1, characterized in that the step of closing said cap (20) is preceded by the steps of purging oxygen from said cartridge (58) and providing a nitrogen overlay in said cartridge.

5 3. The method of claim 1, further characterized by: providing a sleeve (78) having a first open end for receiving said cartridge (58) and a radially inwardly extending stop (84); and placing said cartridge into said first open end of said sleeve such that said cartridge is positively axially retained in said sleeve against said stop.

4. The method of claim 3, characterized by the subsequent step of permanently attaching said sleeve (78) to said cap (20).

5 5. The method of claim 3, characterized in that said sleeve (78) includes a second open end distal said first open end and axially below said sleeve stop, and the step of placing said cartridge into said sleeve is preceded by the step of inserting a plunger rod tip (71) having a head (73) in said sleeve such that said plunger rod tip extends from said second opening and said head is axially adjacent said plunger (54).

6. The method of claim 5, further characterized by the step of capturing said head (73) between said sleeve ledge (84) and said plunger (54).

5 7. The method of claim 1, characterized in that the step of placing the cartridge (58) in a lyophilizing chamber includes supporting said cartridge on a first surface (74), and the step of closing said cap includes exerting a downward pressure upon said cap (20) by contact of a second surface (72) upon said cap induced by relative vertical movement between said first and second surfaces.

8. A cartridge assembly for holding a lyophilized drug and forming a disposable part of an injection pen, the cartridge assembly comprising:

an elongate cartridge (58) having on a first end
5 thereof a shoulder (66), and a rim (63) defining a first
opening and having a circumferential radially outwardly
extending flange (62) adjacent said first opening and a
neck (64) disposed axially between said flange and
10 shoulder, said neck having a diameter smaller than said
flange and shoulder, said cartridge including a second
opening on a second end thereof distal said first opening;

a cap (20) disposed on said first end of said
cartridge, said cap having a first cylindrical portion
including an open bottom received over said first end, a
15 top having an opening therein for receipt of a needle
therethrough, and at least two elastically deformable
ledges (38,40) extending radially inwardly from said first
cylindrical portion and lockingly retained under said neck
flange;

20 a resilient seal (52) in said cap disposed between
said first opening and said top opening and forming an
impermeable barrier therebetween a vent opening in said
cap below said seal; a sleeve (78) radially disposed about
and permanently attached to said cap; and

25 a plunger rod tip (71) slidably disposed in said
sleeve, said plunger rod tip including a head (73) axially
adjacent said plunger for exerting pressure against said
plunger during administration of the drug.

9. The cartridge assembly of claim 8, characterized
in that said sleeve (78) includes a first cylindrical
portion adapted to receive said cartridge and a second
cylindrical portion axially below said first cylindrical
5 portion and concentric therewith, and a radially inward
circumferentially extending ledge (84) defined at the
junction of said first and second cylinder for axially
retaining said one end of said cartridge.

10. The cartridge assembly of claim 8, characterized
in that said rim (63) of said cartridge outwardly tapers
for compressingly sealing said resilient seal (52) between
said cartridge and said cap.

11. The cartridge assembly of claim 8, characterized in that said cap (20) includes an oval shaped wall carrying said ledges (38,40) wherein said wall is thinner along the major axis of the oval than along the minor axis of the oval, and said ledges are disposed generally on the minor axis of the oval.

12. The cap and cartridge assembly of claim 8, characterized in that said deformable ledge comprises two circumferential and inwardly extending ledges (38,40) separated by two arcuate portions of an oval-shaped wall (50) and said ledges are located on the minor axis of said oval-shaped wall.

13. The cap and cartridge assembly of claim 12, characterized in that said oval-shaped wall (50) is thinner along the major axis of the oval than along the minor axis of the oval.

14. A method reconstituting a lyophilized compound, the lyophilized compound contained within an interior space defined by an inner wall of a cartridge (59) having an inlet at one end thereof, the method comprising the steps of: attaching a connector (30) to the inlet end of the cartridge, the connector having an interior space and defining an axis along a longitudinal length thereof, the axis of the connector forming an oblique angle relative to the axis of the cartridge; placing a syringe (96) having a needle (98) and containing the diluent into the interior space of the connector, such that the needle (98) is oriented obliquely toward the inner wall of the cartridge; and injecting a diluent from the syringe into the cartridge via the inlet such that the diluent impinges on and runs down the inner wall of the cartridge before contacting the compound (70) whereby foaming of the compound is prevented.

15. An apparatus for reconstituting a lyophilized drug contained within an inner space of a cartridge, the cartridge (59) having an inlet on one end thereof, and defining a longitudinal axis extending through the inlet,

5 the apparatus comprising: a connector (30) releasably
secured to the inlet end of the cartridge and adapted to
receive and hold a syringe (96) containing a diluent, the
connector having a first portion (111) defining a
longitudinal axis which forms an oblique angle with the
10 longitudinal axis of the cartridge, the syringe being
supported by the connector at the oblique angle whereby
the diluent is injected into the cartridge via the inlet
at the oblique angle.

16. The apparatus of claim 15, characterized in that
said connector (30) is received on the inlet end of the
cartridge, the connector further including a second
portion (113) eccentric with said first portion, said
5 second portion having a larger diameter than a diameter of
said first portion and adapted to retain and support the
syringe.

17. An injector pen and cartridge apparatus for
administering a drug, the apparatus comprising: a
cartridge assembly (90) having a cartridge with a movable
plunger (54) therein and an inlet on one end thereof, said
5 cartridge assembly including a rod tip (71) disposed
axially adjacent said plunger and adapted to exert
pressure upon said plunger for dispensing the drug from
said cartridge, said rod tip including a recess (107) of a
given axial length therein; and an injector pen releasably
10 engaged with said cartridge assembly, said pen including a
movable rod (108) received in said recess (107) and
engaging said rod tip in order to advance said rod tip
during dispensing of the drug; characterized in that said
movable rod (108) has a retraction travel length that is
15 less than the axial length of said recess whereby said
movable rod remains engaged with said rod tip.

18. The cartridge assembly of Claim 17 characterized
in that said plunger rod tip (73) is captured by said
ledge (84) of said sleeve to thereby retain said plunger
rod tip in said sleeve.

1/5




FIG. 1A




FIG. 1B




FIG. 2




FIG. 3




FIG. 4




FIG. 5




FIG. 6




FIG. 7

3 / 5




FIG. 8




FIG. 9

SUBSTITUTE SHEET (RULE 26)

4/5




FIG. 10

SUBSTITUTE SHEET (RULE 26)

5/5




FIG. 11




FIG. 12




FIG. 13




FIG. 14

THIS PAGE BLANK (USPTO)